

H1-The new Generation of Hydrostatics 078 cm³ Single Pumps

Introduction

For more than 40 years, Sauer-Danfoss has been developing state-of-the-art components and systems for mobile machinery used in off-highway operations around the world. We have become a preferred supplier by offering the best of what really matters: The hardware inside your vehicle application. H1 - our new generation of servo-controlled hydrostatic pumps - is no exception.

The H1 range is built around an advanced electrical control and available in a wide range of displacements. It is designed for quality and reliability and offers expanded functionality, greater total efficiency, and easy installation.

All H1 control and sensor options are PLUS+1 Compliant. PLUS+1 allows you to rapidly develop and customize electronic machine control. It opens up the future by combining machine controls and diagnostics in an integrated operating network.

Local Address:



 **PLUS+1** COMPLIANT

*H1 Axial piston pump
Size 078 single pump*

Features

- **Designed for quality and reliability**

- One design concept
- Single piece swash plate

- **Installation and packaging benefits**

- Length optimized pump
- Minimum one clean side
- Higher corner power
- Higher package size ratio
- Standardized connector interface
- Expanded functionality through PLUS+1

- **Optimized for electrical control**

- Electro-hydraulic control options include Electrical Displacement Control (EDC), Forward-Neutral-Reverse (FNR) and Non-Feedback Proportional Electric (NFPE)
- Common control across entire family

- **Expanded functionality**

- PLUS+1 Compliant control and sensor options
- Integral filtration available with integrated filter bypass sensors and switch

- **Greater total efficiency**

- Minimized control losses
- Improved charge circuit
- Lower control pressure for less power consumption

Technical Specifications

Physical properties

Features	Unit	Sizes 078
Displacement	cm ³ [in ³]	78.1 [4.77]
Weight (without PTO and filter)	kg [lb]	56 [123]


Operating parameters

Input speed	Minimum	500
	Rated	3500
	Maximum	4000
System pressure	Maximum working pressure*	420 [6090]
	Maximum pressure	450 [6525]
	Minimum low loop	10 [150]
Case pressure	Rated	3.0 [40]
	Maximum	5.0 [75]

* Applied pressures above maximum working pressure requires Sauer-Danfoss application approval.





T301 072

Schematic



P003 417

Dimensions



Optional: Integrated charge pressure filtration