

PLUS+1™ MC038-010 and MC038-012 Controllers

Mobile Machine Management

MC038-010 and MC038-012 controllers are elements of the flexible, powerful, expandable, and affordable PLUS+1 family of mobile machine management products. These devices are general-purpose controllers that are equally suited for use as members of a distributed machine control system, with intelligence in every node, or as stand-alone controllers.

Product Highlights

Both controllers employ a Digital Signal Processor (DSP), providing the controller with extremely fast single cycle processing speed and 128K internal flash. The MC038-012 has an application key that enables the use of Sauer-Danfoss developed GUIDE machine control solutions. The same GUIDE HWD file is used with both controllers.

Application Development

Users develop MC038-010 and MC038-012 applications with PLUS+1 GUIDE. This Microsoft® Windows® based development environment features a user-friendly, field proven, icon-based graphical programming tool, application downloader, and service/diagnostic tool.

Local Address:



PLUS E1™
by SAUER-DANFOSS


MC038-010 and MC038-012 Controllers

Features

- User-programmable with PLUS+1 GUIDE (Graphical User Integrated Development Environment)
- Power saving sleep mode functionality
- 38 pins: 1 Deutsch® DRC26-38SA connector
- 32 bit fixed-point DSP running at 150 MHz
- 12 bit analog-to-digital converter
- 15 inputs
 - 3 universal (DIN/AIN/FreqIN) that are user-defined as either:
 - Analog:* with configurable ranges 0 to 5.25 Vdc (with over range protection) or 0 to 36 Vdc
 - Digital:* pull up (5 Vdc), pull down (0 Vdc) or pull to center (2.5 Vdc)
 - Frequency (timing):* 1 Hz to 10 kHz
 - 2 digital (DIN) configurable as pull up (5 Vdc), pull down (0 Vdc)
 - 9 digital/analog (DIN/AIN) that are user-defined as either:
 - Digital:* pull up (5 Vdc), pull down (0 Vdc) or pull to center (2.5 Vdc)
 - Analog:* 0 to 5.25 Vdc or 0 to 36 Vdc
 - 1 fixed range analog (AIN/CAN shield) 0 to 5.25 Vdc or CAN shield pin
- 13 outputs
 - 2 DOUT (2 A) configurable as source only
 - 3 HDOUT (6 A) configurable as source only
 - 3 HPWMOUT/DOUT (6 A), configurable as source only
 - 4 HPWMOUT/DOUT (10 A) configurable as source or sink, can be used as bi-directional pairs, (see *Dimensions and Pin Assignments*, back page for pair assignments)
 - 1 HPMOUT/DOUT (10A) configurable as source only
 - Outputs are powered by three independent power supply pins (see *Dimensions and Pin Assignments*, back page for output pin power supply assignments and maximum allowable current per power supply pin)
 - All PWM outputs operate as open loop. The output is a constant voltage.
- 1 independent ECU power supply, 6 to 36Vdc
- 3 independent power supplies for powering output pins, 9 to 36 Vdc
- 1 CAN 2.0B port. The fixed range analog (AIN/CAN Shield) pin may be configured as a shield pin
- 5 Vdc power supply for external sensors rated at 150 mA, monitored and regulated internally
- 2 LEDs under application software control
- MC038-012 contains application key required to run Sauer-Danfoss developed machine control application software
- CE compliant

Dimensions and Pin Assignments

mm [in]




This device is not field serviceable. Opening the device housing voids the warranty.

Caution

PCB damage may occur. All device power supply + pins must be connected to battery +.

Specifications

| | |
|--|--------------------------------|
| Supply voltage, CPU | 6 to 36 Vdc |
| Supply voltage, device | 9 to 36 Vdc |
| Operating temperature, ambient | -40°C to 70°C (-40°F to 158°F) |
| Storage temperature | -40°C to 85°C (-40°F to 185°F) |
| Programming temperature | 0°C to 70°C (32°F to 158°F) |
| IP rating (with mating connector attached) | IP 67 |
| EMI/RFI rating | 100 V/m |
| Weight | 0.53 kg (1.16 lb) |
| Vibration | IEC 60068-2-64 |
| Shock | IEC 60068-2-27 test Ea |
| Device maximum current, sourcing | 70 A |
| Device maximum current, sinking | 25 A |
| Maximum current, power pins: C1-P36, C1-P37, C1-P38 | 25 A per pin |

38 Pin Connector


| Pin | Controller function | Pin | Controller function |
|--------|--|--------|--|
| C1-P1 | CPU power ground - | C1-P20 | DIN/AIN |
| C1-P2 | CPU power supply + | C1-P21 | HPWM/DOUT (6A-Pwr = C1-P37, source only) |
| C1-P3 | CAN0+ | C1-P22 | HPWM/DOUT (10A-Pwr = C1-P37, source only) |
| C1-P4 | CAN0- | C1-P23 | DOUT (2A-Pwr = C1-P38, source only) |
| C1-P5 | AIN/CAN shield | C1-P24 | DIN/AIN |
| C1-P6 | DIN | C1-P25 | DIN/AIN |
| C1-P7 | DIN | C1-P26 | DIN/AIN |
| C1-P8 | 5 Vdc sensor power + | C1-P27 | DIN/AIN |
| C1-P9 | Sensor power ground - | C1-P28 | DOUT (2A-Pwr = C1-P38, source only) |
| C1-P10 | DIN/AIN/FreqIn | C1-P29 | HPWM/DOUT (10A-Pwr = C1-P36, pair with C1-P34) |
| C1-P11 | DIN/AIN/FreqIn | C1-P30 | DOUT (6A-Pwr = C1-P38, source only) |
| C1-P12 | DIN/AIN/FreqIn | C1-P31 | DOUT (6A-Pwr = C1-P38, source only) |
| C1-P13 | HPWM/DOUT (10A-Pwr = C1-P37, pair with C1-P15) | C1-P32 | HPWM/DOUT (6A-Pwr = C1-P36, source only) |
| C1-P14 | DIN/AIN | C1-P33 | HPWM/DOUT (6A-Pwr = C1-P36, source only) |
| C1-P15 | HPWM/DOUT (10A-Pwr = C1-P37, pair with C1-P13) | C1-P34 | HPWM/DOUT (10A-Pwr = C1-P36, pair with C1-P29) |
| C1-P16 | HDOUT (6A-Pwr = C1-P38, source only) | C1-P35 | Output power ground - |
| C1-P17 | DIN/AIN | C1-P36 | Output power supply + |
| C1-P18 | DIN/AIN | C1-P37 | Output power supply + |
| C1-P19 | DIN/AIN | C1-P38 | Output power supply + |

Use care when wiring mating connector.
Above pinouts are for device pins.

Ordering Information

| | |
|------------------------------|----------|
| MC038-010 part number | 11035917 |
| MC038-012 part number | 11076594 |

| Related product | Sauer-Danfoss part numbers |
|--|----------------------------|
| CG150 CAN/USB gateway | 10104136 |
| Deutsch® mating connector bag assembly | 11027919 (16 to 20 AWG) |
| PLUS+1 GUIDE single user license | 10101000 |

Sauer-Danfoss comprehensive technical information **PLUS+1 Controller Family Technical Information, 520L0719** and **MC038-010 and MC038-012 Application Program Interface (API) Document** are on line at: www.sauer-danfoss.com and/or embedded in product HWD file.